V7 L15RM

LCD Specification	15" AU panel
Viewable size	304.1 mm x 228.1 mm
Pixel pitch	0.297 mm x 0.297 mm
Contrast	350:1
Brightness	250 cd/m²
Response time	30 ms
maximum resolution	1024 x 768
recommended resolution	1024 x 768
Color	16.7 Mio.
Horizontal frequency	80 kHz
Vertical frequency	56 - 75 Hz
Adjustment	H/V Position, H/V Size, Language, Reset, etc.
Resolution	640 x 480 @ 75 Hz
	800 x 600 @ 75 Hz
	1024 x 768 @ 75 Hz

Plug & Play	DDC2B
Signal input	15 Pin D-Sub
Power management	EPA, NUTEK
Power consumption	on: 30; suspend: 4; standby: 4; off: 4
Standards	TCO 99, CE, D, S, FI, N, TÜV/GS, ISO 13406-2
Pixel criteria	dark iÜ 3; bright iÜ 2; subpixel total iÜ 5
Monitor dimension (W x H x D)	362 x 345 x 170 mm
	450 x 470 x 125 mm incl. packing
Monitor weight	3.3 kg; 7.0 kg incl. packing
Warranty	3 years onsite service
Features	Kensington-lock, wallmountabel optional, speakers, ultraslim, earphone check
Supply	5 language user's manual, power cable, driver disk, VGA cable, AC/DC cable